

AMENDMENTS TO THE CLAIMS

- Sub
C1
1. (Currently amended) A U-head assembly for rapid and secure attachment to a notched base plate of shoring post apparatus, said assembly comprising:
- a U-head plate having two inwardly opposing L-shaped extensions that form a channel for capturing received in sliding engagement perpendicular to the shoring post to the base plate of the shoring apparatus,
- a latch attached to said U-head plate, said latch having a tongue for engaging the notch in the base plate of the shoring post apparatus upon capture sliding engagement of the base plate of the shoring apparatus within said channel; and
- the latch providing for hand releasable attachment and sliding removal perpendicular to the shoring post of the U-head plate from the base plate.
- B1
2. (Original) The invention in accordance with claim 1 wherein said channel of said U-head is formed by first and second extensions and said latch is attached to one of said extensions.
3. (Currently amended) The invention in accordance with claim 2 wherein said extensions are L-shaped and inwardly opposing thereby forming said a C-shaped channel for capturing the base plate of the shoring apparatus.
4. (Currently amended) The invention in accordance with claim 2 wherein said tongue of said latch engages notch of the base plate of the shoring post apparatus through a hole in one of said extensions.

Sub
C'
5. (Currently amended) The invention in accordance with claim 4 wherein said U-head plate further comprises a first wall and a second wall with a base therebetween, and said extensions extend downwardly from said base of said U-head plate opposite the first and second wall.

6. (Original) The invention in accordance with claim 1 wherein said latch further comprises a spring for biasing said tongue toward the notch of the base plate of the shoring apparatus.

7. (Original) The invention in accordance with claim 6 wherein said tongue of said latch is disengaged from the notch of the base plate of the shoring apparatus by compressing said spring.

B'
8. (Currently amended) A U-head assembly for rapid and secure attachment to a notched base plate of shoring post apparatus, said assembly comprising:

a U-head plate having a first wall and a second wall extending generally upward with a base therebetween, and first and second L-shaped inwardly opposing extensions extending downwardly from said base thereby forming a channel adapted for slidably capturing the base plate of the shoring post apparatus in a direction perpendicular to the shoring post;

a latch attached to one of said extensions of said U-head plate, said latch having a tongue for engaging the notch of the base plate through a hole in one of said extensions upon capture of the base plate of the shoring apparatus within said channel,

wherein said latch further comprises a spring biasing said tongue toward the notch of the base plate of the shoring post apparatus and compression of said spring disengages said tongue from the notch of the base plate of the shoring post apparatus; and

B' 20
C1

the latch providing for hand releasable attachment and sliding removal perpendicular to
the shoring post of the U-head plate from the base plate.
